

Product Data Sheet

Master Format Classification: 07 46 16 Aluminum siding and soffit



Description:	Foiled and sublimated extruded aluminum rainscreen cladding system
Uses:	Prefinished profile aluminum siding and soffit installed to form an exterior rainscreen assembly, or as an interior assembly, using concealed fasteners and extruded aluminum trim and accessory pieces.
Dimension:	6" x 1/2" x 12' & 4" x 1/2" x 12'
Material:	ENAW 6063 T5 Aluminum alloy for marine and offshore building, saltwater resistant
Surface:	High performance woodgrain film for outdoor use
Installation:	With a specially designed self-drilling shoulder screw, which ensures quick and easy assembly, and a tongue and groove connection

Product Attributes and Characteristics:

- Extruded aluminum siding.
- Complete rainscreen system including all necessary clips and trim pieces
- High performance powder coating and sublimation finishes available in an extensive variety of wood grains, metallic, and solid colors; custom colors and finishes also available
- Cladding dimensions allow for field adjustment and thermal movement and expansion.
- Two Siding profiles available: 4" v-groove and 6" v-groove

Selection Criteria:

- Non-combustible (Class A fire rated)
- Maintenance free
- UV resistant
- Corrosion resistant
- 100% recyclable and LEED compliant
- Will not rot, warp, peel, or oil can
- Installer friendly
- No insect infestation
- Anti-microbial
- Non-toxic
- Sold by the box including 4 or 6 pieces without minimum orders
- 10 business day lead time for stock finishes
- Wide array of finishes available
- Offered as a complete extruded aluminum system including necessary fastener and trim pieces for a consistent, high-quality, and full installation

American Society for Testing and Materials International (ASTM):

- ASTM E84, Standard Test Method for Surface Burning Characteristics of Building Material
- ASTM E136, Standard Test Method for Behavior of Materials in a Vertical Tube Furnace at 750°C.
- ASTM E2768-11, Standard Test Method for Extended Duration Surface Burning Characteristics for Building Materials.



International Organization for Standardization (ISO)

- ISO 9227:1990, Corrosion Tests in Artificial Atmospheres – Salt Spray Tests

Packaging, Handling, Protection, Delivery & Storage

- Conform to manufacturer's ordering instructions and lead time requirements to avoid construction delays.
- Will deliver materials and components in manufacturer's cartons, properly labeled and fully identified by product name and brand. Prevents any damage during unloading, storing, and installation.
- Store, protect, and handle materials and components in accordance with manufacturer's recommendations to prevent any damages.
- Store materials off ground and keep clean, dry, and free of dirt and debris. Store away from areas with falling objects or other construction activity that may occur or cause damage.
- Do not store cartons in stacks more than 6 cartons high. Prevent contact with materials capable of causing discoloration, staining, denting, or other surface damage.

Warranty:

All manufacturer's product warranties are against physical defects of systems and products that are properly installed and maintained according to the manufacturer's instructions and recommendations.

- Material: 25 year limited warranty guarantees against buckling, warping, rusting, corroding, and defects in material or workmanship on aluminum siding and soffit.
- Foil: 25 year limited warranty guarantees against cracking, chalking, color retention, gloss retention, and adhesion.

Limitations:

Aluminum cladding must be separated from direct contact with dissimilar metals.

SAFETY:

When dealing with any type of construction project, it is necessary to wear appropriate safety equipment to avoid any risk of injury. It is recommended but not limited to the following safety equipment being used when handling, cutting, and installing Lynx Siding: gloves, respiratory protection, long sleeves, pants, and safety glasses. More information about personal protective equipment is available at:

www.osha.gov/SLTC/personalprotectiveequipment

Availability:

Depending on project location, product is available directly through the appointed distributors.

Cost:

Contact appointed distributors for product and related costs.

PRODUCT PROPERTIES

MATERIALS, COMPOSITION, PROPERTIES

Material: 6063-T5 aluminum alloy
architectural grade extruded aluminum

Trim Pieces, 6063-T5 alloy extruded
aluminum

@ 10' (3050 mm) lengths

- H-Mold
- J-Mold
- Windows J-Mold
- Outside Corner
- Inside Corner

Other Components, 6063-T5 alloy extruded aluminum

@ 10' (3050 mm) lengths

- Hat Channel
- Hat Channel Vented
- Starter Strip

Fasteners

- 1" length Shoulder Screw

Others:

Touch Up Pen



PROFILE SHAPE, MASS, AND DIMENSION

4" V-Groove Siding and Soffit

- Size: 4" profile face
- @ 12' lengths
- Thickness: 15 gauge aluminum
- Weight: 6.2 lbs per 12' piece
- 1.6 lbs/ft²

6" V-Groove Siding and Soffit

- Size: 6" profile face
- @ 12' lengths
- Thickness: 15 gauge aluminum
- Weight: 11.25 lbs per 12' piece
- 1.9 lbs/ft²



FINISHES

Selected by owner's representative from manufacturer's range

- Solid color and metallic finishes: foiled
- Decorative finishes (i.e. wood grain): foiled

PRODUCT PLACEMENT

PREPARATION

- Obtain dimensions and material take off measurements from job site before ordering product and fabricating material.
- Ensure structural support is properly aligned, installed correctly, and condition is acceptable and ready to receive cladding system. Review drawings that indicate areas to be clad with system.
- Building surfaces shall be smooth, straight, aligned, clean, dry, and free from defects detrimental to the flush and proper installation of the aluminum siding system. Notify Contractor of conditions not acceptable for installation of the system.
- Inspect product before installation and verify that there is no shipping damage; ensure proper handling and storage of all material.
- Do not install any damaged or questionable product; repair or replace as required for smooth, consistent, and high-quality finished appearance.

INSTALLATION

- Ensure the requested amount of product has been received. Notify the manufacturer if order has not been properly filled.
- Install cladding and components in accordance with project drawings, and manufacturer's installation instructions.
- Ensure continuity of building envelope air barrier and vapor barrier systems.
- Do not install over cementitious materials, dissimilar metals, or pressure treated material without adequate barrier protection.
- Install starter strips, trims and corner pieces as required, in accordance with best practice, with all members plumb and true.
- Install siding and soffit material as required, maintaining joints are true to line, tight fitting, hairline joints. Locate joints over supports or use splicer piece as required to ensure structural stability. Fasten to supports using rain screen clips in an aligned, level, and plumb manner, using spacing recommended by manufacturer's installation instructions.
- Fasten and install components in a manner that does not restrict thermal movement. Coordinate installation with other outside components that relate to the cladding system.
- Install expansion control joints where indicated
- Apply isolation coating if areas of contact between dissimilar metals is otherwise unavoidable.
- Use the appropriate colored touch up pen to cover cut ends of exposed aluminum.

CORPORATE IDENTIFICATION LYNX DESIGNS

Head Office

Address: 4035 Cheyenne Ct, Chino, CA 91710, USA

Phone: 1 909 393 2800

Email: info@lynx-designs.com

Website: www.lynx-designs.com

TECHNICAL SERVICES AVAILABLE

For technical inquiries, please contact manufacturer directly

CLASSIFICATION AND FILING

Master Format: 07 46 16 – Aluminum Siding